


TAURUS K310w/K320w

QUICK START GUIDE

用户指南

ABOUT DEVICE





O / SHORTCUT KEYS

| *1 | Fn+Q | Switch to Bluetooth device 1 |
|----------|----------|---|
| *2 | Fn+W | Switch to Bluetooth device 2 |
| 2 | Fn+E | Switch to 2.4GHz wireless connection mode |
| Å | Fn+R | Switch to USB connection mode |
| 7 | Fn + F12 | Invoke the on-board configuration profile |

02 / INDICATOR LIGHTS

| КЗІОш | | | | | | |
|--------------------|--|--|--|--|--|--|
| Indicator Light | Normal Indicator Status * | Wireless Connection Status Indicator ** | | | | |
| 1 | Number Lock Indicator Light | | | | | |
| A *1 | Caps lock indicator | Bluetooth device 1 connection status indicator | | | | |
| □ * ₂ | Windows Key Lock Indicator (FN+L-WIN) | Bluetooth device 2 connection status indicator | | | | |
| | Configuration profile indicator | 2.4GHz wireless connection status indicator | | | | |
| Ē | Battery indicator | | | | | |

| К320ш | | | | | | |
|--------------------|--|--|--|--|--|--|
| Indicator Light | Normal Indicator Status * | Wireless Connection Status Indicator * * | | | | |
| A *1 | Caps lock indicator | Bluetooth device 1 connection status indicator | | | | |
| □ * ₂ | Windows Key Lock Indicator (FN+L-WIN) | Bluetooth device 2 connection status indicator | | | | |
| ⊕ ≥ | Configuration profile indicator | 2.4GHz wireless connection status indicator | | | | |
| Ð | Battery indicator | | | | | |

 When K310w/K320w is successfully connected and functions normally, the indicators lights should also work normally.

** When K310w/K320w pairing is available, the corresponding indicator light flashes quickly.

When K310wlK320 wis paired but cannot connect, the corresponding indicator light flashes slowly. Please check if the device to be connected is functioning normally.

When K310w/K320w is successfully connected, the corresponding indicator light will be on for 3 seconds and then revert back to the normal indicator status.

03 / WIRELESS SWITCH







CONNECTION SPECIFICATIONS

| ı | KEYBOARD | |
|---|-----------------|---|
| | BLUETOOTH | Frequency range: 2402MHz-2480MHz Transmitter power: < -2.5dBm |
| | 2.4GHz WIRELESS | Frequency range: 2402MHz-2480MHz Transmitter power: < -0.5dBm |
| | RECEIVER | |
| | 2.4GHz WIRELESS | Frequency range:2402MHz-2480MHz Transmitter power: < 3.5dBm |

BLUETOOTH CONNECTION

Enter Bluetooth mode by pressing FN+Q/W.

3

The corresponding indicator light flashes quickly upon initial use. Search for K310w/K320w on a device that supports Bluetooth low energy technology and complete the pairing according to the on-device prompts. The corresponding indicator light will be on for 3 seconds and then revert back to the normal indicator status. If re-pairing is needed, long press FN+O₂W for 3 seconds until the indicator light flashes quickly, and then users can proceed with re-pairing.

2.4GHz WIRELESS_CONNECTION

Tum on wireless switch.

ON/OFF

ON

Plug in the wireless receiver.



3

fn E

Press FN+E to enter 2.4GHz wireless connection mode, after which the device will connect automatically. The indicator light will be on for 3 seconds and then revert back to the normal indicator status.

USB WIRED CONNECTION



2 fn R

Press FN+R to enter USB wired connection mode.

LEARN MORE

Check out www.durgod.com and download "Durgod Zeus Engine" to get:

- The latest firmware updates
- Entire key customization
- Macro editing function
- On-board and cloud storage of configuration profiles
- The latest information on Durgod products





Zhuhai Hoksi Technology CO.LTD

Room803,NO.3 building,NO.6,Pingbei 1Road,Nanping,Technology & Industry Park,Xiangzhou District.Zhuhai City.China

Copyright © 2017 Zhuhai Hoksi Technology CO., LTD.ALL rights reserved. All copyrights or trademarks are the property of their

REGULATORY AND COMPLIANCE-INFORMATION

■ FCC STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCF clules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interfere by one or more of the followine measures:

- -Reorient or relocate the receiving antenna.
- -Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to
- which the receiver is connected
- -Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement

This device complies with FCC radiation exposure limits set forth for an uncontrolled environment and it also complies with Part 15 of the FCC RF Rules. This equipment must not be co-located or operating in conjunction with any other antenna or transmitter. End-users and installers must be provide with antenna installation instructions and consider removing the no-collocation statement.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference
 - this device must accept any interrerence that may cause undesired operation.

Caution!

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

■ STATEMENT OF COMPLIANCE WITH EU DIRECTIVE

Hereby, Zhuhai Hoksi Technology, LTD.,CO declares that the radio quipment type DURGOD K310w/K320w Wireless Mechanical Keyboard is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: http://www.dureod.com

CAUTION:

(1) Risk of fire or explosion or defeat the safeguard of equipment if the battery is replaced by an incorrect type. Replace only with the same or equivalent type.

(2) Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

(3) High or low extreme temperatures or low air pressure at high altitude that the battery can be subjected to during use, storage or transportation.

(4) Leaving the battery in an extremely high temperature and/or low air pressure surrounding environment that can result in an explosion or the leakage of flammable liquid or as.

保僧服务卡

| 产品型号 | |
|---------|---------|
| 购买日期 | |
| 用户姓名 | |
| 联系电话 | |
| 通讯地址/邮编 | |
| 产品S/N码 | 质量检验 合格 |



厂商:珠海市学思电子科技有限公司 地址:珠海市香洲区南屏科技园屏北一路6号南裕丰大厦8楼

保修服务指南

■ 感谢您对DURGOD(村伽)的信任与支持

DURGOD将为您提供一年的产品免费保修服务,请勿擅自涂改本保修 服务卡,以维护您的合法权益。如需服务或技术支持,请咨询相关经销 商或与我们联系。

■ 我们承诺

对保修期间内及在保修服务范围内的产品,DURGOD将按照本服务政策进行维修、更换或退货在合理的时间内免费为您恢复产品的正常使用功能;对超出保修期和保修服务范围之外的产品,DURGOD将按照本服务政策提供有偿维修服务。

■ 保修服务时须提供

- 1、申请保修的DURGOD产品或附件。
- 2、有效的购买凭证。

■ 质保不包含一下原因导致的问题和损坏:

- 1、产品正常使用磨损。
- 2、由于人为原因造成的损坏,包括但不限于因跌落、挤压、碰撞造成的损坏,因液体泼溅、化学品腐蚀、异物进入内部造成的损坏。
- 3、因使用、保养、维护不当造成的损坏。
- 4、产品被任何未经授权方拆除、维修、批次号去除、涂改至难以辨认等。
- 5、产品超出保修期。
- 6、因不可抗力损坏。




кзіош

| | | | | | | | | | | | | | | | | | | î û | |
|----------|---|-------|---|----|-----|---|---|---|---|-----|------|----|----|---|-------|---|---|-----|---|
| | | | | | | | | | | | | | | - | | | | * | |
| ws | q | ŵ | È | RT | Y | Ü | Ė | 0 | ľ | TT: | | | 14 | | ~~ | 7 | : | | |
| | A | 8 | 0 | 7 | G H | J | K | Ì | | | - in | | | | | 4 | 1 | | |
| 0.00 | | X | C | A | 8 | я | × | | | 177 | 911 | - | | 1 | | 1 | 2 | 3 | ī |
| me III e | | At II | | | | | | | - | | B | 24 | | | 17.00 | | | | |

K320m





○ | /快捷键

| *1 | Fn+Q | 切换蓝牙设备 1 |
|----------|---------|------------|
| *2 | Fn + W | 切换蓝牙设备 2 |
| 2 | Fn+ E | 切换2.4G无线模式 |
| Å | Fn+R | 切换USB模式 |
| F | Fn+ F12 | 调用板载配置文件 |

02 /指示灯

| КЗІОш | | | | | |
|--------------------|----------------|----------------|--|--|--|
| 指示灯 | 正常指示状态 * | 无线功能状态 ** | | | |
| 1 | 数字键区指示灯 | | | | |
| A *1 | 大小写指示灯 | 蓝牙设备1 连接状态指示灯 | | | |
| □ * ₂ | 锁键(Fn+左Win)指示灯 | 蓝牙设备2连接状态指示灯 | | | |
| | 配置文件指示灯 | 2.4G 无线连接状态指示灯 | | | |
| P | 由最指示灯 | | | | |

| | К320ш | | | | | | |
|--------------------|----------------|----------------|--|--|--|--|--|
| 指示灯 | 正常指示状态 * | 无线功能状态 ** | | | | | |
| A *1 | 大小写指示灯 | 蓝牙设备1连接状态指示灯 | | | | | |
| □ * ₂ | 锁键(Fn+左Win)指示灯 | 蓝牙设备2连接状态指示灯 | | | | | |
| | 配置文件指示灯 | 2.4G 无线连接状态指示灯 | | | | | |
| Ð | 电量指示灯 | | | | | | |

- * 当 K310w/K320w 已完成连接并可正常使用时。指示灯进入正常指示状态。
- ** 对应连接模式处在可配对状态时,指示打快风。 对应连接模式处在已配对但是无法进联水态时,指示打侵风,此时请检查对应的连接设备是否正常。 对应连接模式或指连接上时,指示打落头的后,退入正常指示状态。

03 /无线开关



连接参数

| 键盘 | |
|----------|------------------------------------|
| 蓝牙 | 频率范围:2402MHz-2480MHz 发射功率:<-2.5dBm |
| 2.4GHz无线 | 频率范围:2402MHz-2480MHz 发射功率:<-0.5dBm |
| 接收器 | |
| 2.4GHz无线 | 频率范围:2402MHz-2480MHz 发射功率:<3.5dBm |

蓝牙设备连接

■ 天线开关外于ON的状态。



2




FN+Q / W进入蓝牙模式。

3

初次进入蓝牙模式,对应的指示灯铁闪,在支持蓝牙低功耗技术的设备上搜索设备,根据 设备提示完成配对,对应指示灯常亮3秒后恢复正常指示状态。如需重新配对,长按 FN+Q/W 3秒直至对应指示灯铁闪,则可重新进行配对。

2.4G 无线连接

■ 无线开关处于ON的状态。



3

Po | - | E

FN+E进入2.4G无线模式,设备自动完成连接,对应指示灯常亮3秒后恢复正常指示状态。

USB有线连接



2



FN+R讲入USB模式。

获取更多

访问http://www.durgod.com,下载DURGOD ZEUS ENGINE,您将获得:

- * 最新的固件升级
 - * 全键盘按键自定义
- * 宏编辑功能
- * 配置文件板载存储与云存储
- * 最新的产品咨询





■ WeChat

珠海市学思电子科技有限公司

珠海市香洲区南屏科技园屏北一路6号南裕丰大厦8楼

客服电话:400-678-3313 客服部箱:service@durgod.com

技术支持:suppot@durgod.com